

MARKET FOCUS: ROADSIDE-CONSTRUCTION- UTILITIES DEVICES

STANDARD DEVICES Each device features all white front LEDs (8), solid or split color rear LEDs (8), a single red LED work light in the front (1), and a white LED light on top (1). Hybrid Models have a single Infrared LED on the top instead of white (1). Each side has flashing, strobing and constant-on light patterns which can be independently controlled.



ELT-W/GY WHITE / GREEN YELLOW
ELITE SERIES



ELT-W/Y WHITE / YELLOW
ELITE SERIES



ELT-W/O WHITE / ORANGE
ELITE SERIES



ELT-W/BY WHITE / BLUE YELLOW
ELITE SERIES

BEACON DEVICES Each device features solid or split color front LEDs (8), solid or split color rear LEDs (8), a single white LED work light in the front (1), and a white LED light on top (1). Each side has flashing, strobing and constant-on light patterns which can be independently controlled.



ELT-GY/GY GREEN YELLOW / GREEN YELLOW
ELITE SERIES



ELT-WY/WY WHITE YELLOW / WHITE YELLOW
ELITE SERIES

MICRO DEVICES Each device features white or solid color front LEDs (4), solid color rear LEDs (5), a single white or red LED work light in the front (1), and a white LED light on top (1). Each side has flashing, strobing and constant-on light patterns which can be independently controlled. Compatible with all Elite Mounting options.



MCR-W/Y WHITE / YELLOW
MICRO SERIES



MCR-W/R WHITE / RED
MICRO SERIES



MCR-Y/Y YELLOW / YELLOW
MICRO SERIES



- **LIGHT SOURCE** Elite 18 LEDs, Micro 11 LEDs
- **COLOR OPTIONS** Elite 25 Combinations: Red, White, Blue, Yellow (Amber), Orange, Green, Infrared
Micro 11 Combinations: Red, White, Yellow (Amber), Orange, Green, Infrared
- **BRIGHTNESS** Elite: up to 800 Lumens, 5+ Miles Visibility
Micro: up to 500 Lumens, 3+ Miles Visibility
- **IR (INFRARED)** Hybrid- single 850nm infrared LED on top
All-Infrared - 940nm infrared LED
Can only be seen using night vision equipment
- **BRIGHTEST COLORS** White, Green, Yellow
- **SIZE** Elite: 2.75"W x 1.87"H x 1.0"H, Micro 1.99"W x 1.72"L x 0.68"H
- **WEIGHT** Elite: 3.25oz, 92.4g, Micro 2.0oz 56.70g
- **BATTERY** Type: Rechargeable Lithium Polymer
Capacity: Elite: 1400mAh / 5.18Wh, Micro 500mAh / 1.85Wh
Normal Voltage: 3.7V
Certification: UN38.3
Run Time/Charge: Elite 1.5 - 150 hrs, Micro 1.0 - 50 hrs
Most common settings Elite 8-12 hrs, Micro 1-3 hrs (continuous)
Battery Life Cycle: Elite 1500 - 3000, Micro 500-3000 cycles w/ regular use
- **CHARGING** Cord: Type-C to USB
Input: AC 100-240V - 50/60Hz, 0.6A
Output: 5.0V - 2000mA
Charging Time: Elite Approx 1.5 hrs, Micro Approx 50 min.
- **CASING** Material: Polycarbonate Lens, Glass Filled Polycarbonate
Exterior Covers & USB Door, High Temperature
Rubber Buttons & Water Seals Hz, 0.6A
IP Rating: Elite IP68 Water/Dust Proof Rating,
Micro IP67 Water/Dust Proof Rating
Flammability Rating: UL 746B, UL94
- **MOUNTING** Neodymium iron boron Grade NB42 Magnets
Optional Hard Mount on select mounts using (2) M3 screws
- **ENVIRONMENT** Operational Temp & Humidity: -40°C -110°C, -40°F - 230°F
Storage Temp & Humidity: 20-28°C, 68-82°F

MARKET FOCUS: ROADSIDE-CONSTRUCTION- UTILITIES MOUNTS



	SKU	NAME	APPLICATION	FEATURES	FITS STRAPS UP TO	UNDER STRAP BASE WIDTH	MORE HM: Hard Mounting Option SC: Hard Mounting Screws Included
	ACC-HHM	Hard Hat Mount	Hard Hat / Helmet	Magnet Disk applies to inside of the helmet w/ adhesive			
	ACC-MCM	Magnetic Cone Mount	Traffic Cones	3-leg design allows the mount to be inserted into any size cone			HM
	ACC-UCM	Universal Clip Mount	Radio Strap, Belt, Hat brim, Epaulet, Molle	Works well w/ wider straps, rubber backing for better grip	1/4" thick and over 2" wide	0.75"	HM, SC
	ACC-UCMS	Small Universal Clip Mount	Radio Strap, Belt, Hat brim, Epaulet, Molle	Works well w/ wider straps, Strong clip tension, able to hang on a wall screw	1/8" thick and over 1.5" wide	0.75"	HM
	ACC-WM	Window Mount	Windshield, Dash	2.5" Suction Mount			
	ACC-HHMS	Helmet Strap w/ 2 Magnetic Mounts	Fire Helmets, Thicker Hard Hats, Safety Helmets	28" x 7/8" stretch adjustable strap		0.8"	HM, SC
	ACC-MMB	Base Shoulder Mount	Under clothing & straps	Padded bottom for comfort	Strap guides are 1.75" wide	2.125"	
	ACC-MSML ACC-MSMS	Arm Strap w/ Magnetic Mount	Arm or Over Clothes	19.5" x 2" OR 15" x 2" Adjustable Velcro strap		2"	
	ACC-DTS	Device Tether	Device Loss prevention / added security	8.5" Total length, Quick disconnect, Carabiner & Cord Lock			